

General Equipment

850 Open

SPECIFICATIONS

L.O.A* : 9.75 m Length of hull: 8.50 m Width of hull: 3.30 m Weight: 4 500 kg Draft: 0.85 m Minimum air draught on sea : 3.10 m Fuel tank capacity : 550 l Water tank capacity: 200 l Engine : single or twin-engined single Maximum engine power single engine : 440 HP Maximum engine power twin-engined : 2 x 225 HP Transmission : propeller shaft EC certification : B8 / C10 Architects : Joubert-Nivelt Designer : Olivier Flahaut * with swimming platform and bow-fishing gangway options

STANDARD EQUIPMENT

Construction

Hull and deck reinforced polyester laminate Wooden bulwark rail and rubbing strakes Superstructure : cellular sandwich Hull bottom : balsa sandwich Deck : 12 mm marine ply sandwich Stainless steel keel strip

Deck equipment

Self-draining chain locker Stem-head anchor roller 2 fairleads fore and aft 2 mooring cleats fore and aft 2 stainless handrails on coachroof 2 deck hatches for cabin ventilation Stainless bow pulpit 4 opening cabin portholes 1 stainless mast to carry antennae and radar 1 fore deck bench seat for 4 Recessed fuel filler

Engine facilities

Diesel engine, prop shaft drive with protected propeller Soundproofed engine compartment 550-litre fuel tank Engine casing fitted with electric lift

Cockpit & deck

Self-draining cockpit 3.00 m x 2.60 m Roomy foredeck for sunbathing Transom door Teak cabin door 1 aft deck bench seat for 3 3 folding bench seats
1 engine casing
1 aft cockpit locker
1 stern locker (access to hydraulic steering ram)
1 emergency tiller
2 rod-holders
Eyelets for fenders
Manual bilge pump
Bathing ladder

Helm position

Stainless-framed windscreen with handrail 1 hydraulic steering wheel 1 pilot and copilot bench with stowage Engine controls Engine control panel Instrument console Steering compass Step 2 windscreen wipers

Cabin

1 fitted galley Sink with pressurized water 2-burner cooker Microwave 150-litre water tank 85-litre refrigerator Cupboards, drawers and shelves Bar unit with stowage for bottles + glasses 1 armchair Saloon table converting into double berth Double berth forward 3 stainless opening portholes 2 forward deck hatches Side cubby-holes Lockers under berth

Head

Wash-basin with pressurized water Sea toilet with holding tank Shower Cupboard - hanging locker - mirror 1 stainless opening porthole

Electrical facilities

1 x 12 volt, 105 amp battery per engine 2 x 12 volt, 105 amp battery for services Control panel with engine battery isolator Cabin and head lighting Navigation lights Bilge pump