EXTERIOR

Construction

- Solid laminate hull and barrier coat to prevent against osmosis
- · Hull with structured and glued innner mould
- Prisma Process® injected deck
- L-shaped cast iron keel
- Rudder with foam core and GRP skin, composite rudder shaft

- Standard mainsail (furling) $48 \, \text{m}^2 / 516 \, \text{sq ft}$
- Standard genoa 109 % $63 \,\mathrm{m}^2 / 678 \,\mathrm{sg} \,\mathrm{ft}$

Mast and rigging

- Deck-stepped, anodised aluminium in-mast furling mast, fractional rig built by Z-Spar
- Double spreader design
- Anodised alumiunium boom
- Facnor® genoa furler
- Rigid boom vang
- · Standing rigging made of discontinuous stainless steel cable
- Running rigging: halyards and sheets in Dyneema, additional lines and sheets in polyester

Sailing features

- Spinlock® line stoppers
- Harken® Genoa Tracks with genoa sheet cars
- Harken® turning blocks
- 2 Harken® 46.2 ST winches
- 2 Harken® 70.2 ST winches

Deck

- Open bow pulpit
- Double stainless steel lifelines
- Stainless steel double anchor roller
- Anchor windlass 1500 W
- Anchor locker with drain
- Mooring cleats (6)
- Sail locker access
- Opening deck hatches (10)
- · Lateral coachroof windows
- Opening ports integrated behind fixed windows (2)
- · Main chainplates in stainless steel at deck edge
- · Folding padeyes on deck

Cockpit

- Double leather-covered stainless steel steering wheels
- Lounge chair on both sides of the companionway
- · Cockpit table with integrated freezer
- Liferaft locker
- 2 backstay chainplates
- Cockpit lockers (4)
- Gas locker (2 bottles)
- Large Teak aft fold-down swim
- Teak inlay on bench seats, cockpit floor, steps and transom platform
- Stainless steel handrail
- Shore power socket

 Drop-down companionway hatch (plexiglass)

Sail locker forward

- · Access through lockable deck hatch
- Access ladder
- Shelving along hull sides for storage
- Access to bow thruster and technical areas
- LED lighting

INTERIOR

Saloon

- Seating arrangement on starboard (7 guests)
- Overhead lockers above seating
- Hinged storage compartments under seatings
- Saloon table with two removable legs convertible to double berth
- Short legs, saloon backtest to be used as mattres for double berth
- LED lighting with dimmer
- Fixed hull ports (2)
- Low-profile opening hatches (4)

• Long galley to port with Corian® counter top

- Aft galley to starboard with Corian® counter top
- Double stainless steel sinks with removable covers
- Chromed mixer tap
- Foot pump with separate tap, Y-valv to select fresh or sea water
- Drawers with shock absorbers and storage units
- Retractable waste bin
- Gas oven cooker with 2 burners with removable top counter
- 250 L / 66 US gal combination fridge / freezer 12 V
- Handrails
- Dust pan integrated into the floorboard

Utility room

(standard / located between galley and starboard aft area)

• Hanging locker and storage cabinets

Chart table

- Ergonomic and seaworthy seat
- Chart table with opening compartment
- Upper storage compartment
- · Bicolour reading light
- Navigation and level control screens

Forward cabins

Owner's stateroom

- Double berth (2,03 x 1,60 m / 6'7" x 5'2")
- Lateral bunks
- Hanging locker with storage drawers
- · Assisted opening storage cabinet
- Storage drawers under berth (2)

- LED reading lights and lighting
- Bedside tables
- Fixed hull ports with sliding shades (2)
- Deck hatches (4)
- En-suite toilet / shower room

Double symmetrical modular cabins

- Double berth (2,03 m x 1,56 m / 6'7" x 5'1")
- Removable bulkhead, to be stored under the beds
- Double hanging locker with storage lockers
- Upper storage cabinet under the side decks
- Under-bed storage AC and USB plugs
- LED reading lights and lighting
- Fixed hull ports with aviation shades
- Opening deck hatches (2)
- En-suite toilet / shower compartment

Aft cabins

Port VIP cabin

- Double berth (2,03 m x 1,50 m / 6'7" x 4'11")
- Sofa
- Hanging locker
- LED reading lights and lighting
- Bedside tables
- Fixed hull port with aviation shade
- Opening ports (2)
- En-suite toilet / shower room

Starboard guest cabin

- 2 single berths (2,05 x 0,70 m /
- Hanging locker
- Indirect LED lighting
- Opening ports (2)
- En-suite toilet / shower room

Starboard side cabin

- \bullet Twin bunk (2,05 m x 0,70 m / 6'5" x 2'3")
- Hanging locker with shelving
- Under-bed storage
- LED reading lights and lighting
- Opening port

TECHNICAL EQUIPMENTS

Flectric

- Main electric panel at navigation station backlighted with a soft blue light
- Switches for domestic systems
- 12 V plug
- LCD displays: DC Voltage level, amperage consumption meter, fuel and water gauges
- House batteries bank (4 x 115 Ah / 12 V)
- 12 V) Engine alternator 12V / 125 Ah
- Engine battery bank (1 x 120 Ah /

• Battery switches: in compartment to starboard of the companionway

- 12 V and 230 V or 115 V plugs in each cabin, saloon, galley and at chart table
- LED lightings

Motorization

- YANMAR® 4JH4TCE Sail Drive 80 HP - 59 kW
- Sound insulation
- GRP engine bed and liner
- Fixed 3-blade propeller
- Roto moulded exhaust box, stainless steel exhaust fitting on hull
- Extractor fan located in engine room.
- Ventilation ducting vents on transom
- Roto moulded tank 240 L/ 63 US gal
- Inline fuel / water separator
- Fuel gauge at electrical panel

Plumbing

Fresh water

- Fresh water system, high-pressure 12V pump (19 L/min or 5 US gal / min), inline filter and accumulator tank
- 400 L / 106 US gal tank under the forward berth
- 240 L / 63 US gal tank under aft cabin berth
- Tank gauges (1 per tank)
- Manifold to select the water tanks
- 40 L / 11 US gal hot water heater • Hot and cold cockpit shower

drained overboard

22 US gal in each head

- Raw and waste waters • Shower pumps with macerator,
- shower pumps switch · Sinks and washbasins directly
- Manual marine toilets with large bowl • Roto moulded holding tank 85 L/
- Hoses built in high quality White

- Bilge drainage • Automatic electric bilge pump with
- manual switch at ythe electrical panel · Manual bilge pump located in cockpit

HEADROOM

- Master forward cabin 1,98 m / 6'6" • Aft guest's cabin(s) 1,97 m / 6'6"
- Aft VIP's cabin(s) 1,97 m / 6'6" Companionway 2,07 m / 6'9"
- Galley 2,05 m / 6'9" • Forward owner's head 2,02 m / 6'8"
- Aft VIP's head 2,13 m / 6'0"